Product data sheet

RUNDO24 290-251K-10GGM3/830, S
290-251K-10GGM3/830
HALLA



IP 20

290-251K-10GGM3/830, S Luminaire surface/wall mounted/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 501 x 501 x 24 mm Type of installation: Surface, Wall mounted, Suspended Distribution: Direct-indirect Optics type: Opal diffuser Protection class: I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	230 lm	LOR	100%
Luminous efficacy	153 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28.1 W	CRI	80
Total flux	3570 lm	LOR	100%
Luminous efficacy	127 lm/W	Total power	28.1 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Height: 0.94 in
Diameter: 19.69 in

Adjustability

Fixed

Electric

System power: 29.6 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 20