


Product data sheet

ECO-PANEL BL 295X1195 34W UGR <19


40000162

PROLUMIA




Light source: SMD 2835 LED Beam angle: 120° Color temperature: Switchable 3000K, 4000K en (and) 6000K Light output: Respectively 3750Lm, 4080Lm en (and) 4080Lm Color rendering index: Ra>80 Operating temperature: -20°C - +50°C Rated life hours: >50.000 (>50,000) LED current: 900mA Input: 220-240V, 50-60Hz Power factor: >0,95 (>0.95) Power consumption (driverincluded): 34 W Electrical safety class: Class II Driver: Various drivers, dimmable or not, can be ordered separately with or without power cord.

Light output 1




1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4080 lm	Total flux	4080 lm
Luminous efficacy	120 lm/W	Total power	34 W
CCT	6500 K		
CRI	80		



1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4080 lm	Total flux	4080 lm
Luminous efficacy	120 lm/W	Total power	34 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	34 W	LOR	100%
Lamp flux	4080 lm	Total flux	4080 lm
Luminous efficacy	120 lm/W	Total power	34 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 34 W

Appliance Class: 0

Shape and measurements

Length: 47.05 in

Width: 11.61 in

Height: 1.26 in

Protection

IP: 20

Designation labels: CE