Product data sheet


RAX SOFT 150 SATIN 2800LM (@800MA) 3000K RA>90 UGR<22
7021982125072
SG ARMATUREN



IP 20 IK 08

Rax Soft 150 is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with satin matt reflector for high efficiency. Rax Soft 150 is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm. Light distribution Direct Light technic LED 30W (@800mA) 3000K Ra>90 SDCM 2 L90/B10 >100,000 hrs Optic Satin Matt Reflector Control/Dimming DALI Protection Class II SELV IP20 IK08 Materials and finish Housing: Flame retardant polycarbonate Colour: Satin matt Optics: PMMA Polymethylmethacrylat Mounting/Connection Recessed (downlight), Indoor Cable 3x0,75mm² Quick connector Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	2800 lm	Total flux	2801 lm
Luminous efficacy	93 lm/W	Total power	30 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.54 in
Width: 6.54 in
Height: 3.27 in

Adjustability

Fixed

Electric

System power: 30 W
Appliance Class: II

Protection

IP: 20
IK: 08