


Product data sheet

SPORTS LIGHTING

V1-P1-702X2-04D50-6528050 AIRQUB SPORT 280 W 280W 5000K TRANSPARENT DALI ASYMMETRIC AS1
VARTON




IP
67

IK
01

High-power floodlight with a wide range of wattage and optics. Best lumens/mass/size ratio in its class of solutions. Material: Cast aluminum radiator, steel body parts, acrylic optic. Installation: Surface-mounted using an adjustable bracket. The mounting bracket has an angle of inclination 30° to the horizontal for comfortable aiming of the spotlight. Angle of rotation: 30° to 165° in 5° increment. Application: Outdoor areas. Industrial facilities. Sports lighting. Flicker, %: 1 Input voltage (AC, 50Hz), V: 90...305 AC frequency, Hz: 50 Input voltage (DC), V: 127...250 Climatic modification and category of placement: УХЛ1 Ingress protection (IP): IP67 Protection class: I Impact resistance: IK01 Power factor: 0,95 <https://www.varton.ru/products/sportivnoe-osveshchenie/airqub-sport/airqub-sport-280-vt/svetodiodnyy-prozhektor-var-ton-airqub-sport-280-vt-5000-k-as1-dali/>

Light output 1



1 x LED			
Nominal lamp power	280 W	LOR	100%
Lamp flux	39500 lm	Total flux	39500 lm
Luminous efficacy	141 lm/W	Total power	280 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 280 W

Shape and measurements

Length: 20.63 in

Width: 13.23 in

Height: 15.24 in

Protection

IP: 67

IK: 01

Adjustability

Fixed