


Product data sheet

3385 COMO 3 - CYCLE LANE 4000K CRI 70 9W CLD ANTHRACITE
340570-30
DISANO



Housing: die-cast aluminium, designed with a very small surface exposed to wind. Attachment: suited for poles with a diameter between 60 and 76 mm. Optics: in high-performance PMMA resistant to high temperatures and UV rays. Diffuser: tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - waterproof connector for quick installation with no need to open the fixture. - anti-condensation valve. - temperature controller with auto-reset. - EN 61547 compliant surge protection. - CLD PROG built-in functions.

Light output 1



1 x LED			
Nominal lamp power	9 W	LOR	100%
Lamp flux	1440 lm	Total flux	1440 lm
Luminous efficacy	160 lm/W	Total power	9 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Height: 24.41 in

Diameter: 16.54 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: Anthracite / graphite

Electric

System power: 9 W

Appliance Class: II

Protection

IP: 66

IK: 09

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -22...104°F