Product data sheet

SRT-SYSTEM IP20-SRGVCDA EP/1500 LED - GERÄTETRÄGER VARIABEL CENTRAL.LINE.OPTIC | DEVICE MOUNT VARIABL.. 13000 865 DALI2 VW RAL 9016 (SRT+19565006940)

REGIOLUX

IP 20 IK 03

SRT-Quick-fit mounting system, Variable device mount, Modullänge/1500. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Variable position on the mounting rail. Housing colour traffic white RAL 9016. Performance level: Economy Performance (EP) - For cost-sensitive projects, high efficiency and a long service life, Light distribution direct double asymmetrical distribution by means of Central.Line.Optic of PMMA plastic, the lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The compact 1-row arrangement of the lenses ensures that the dots merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1531mm x 55mm x 37mm Beam angle: 80°(C0)/100° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 6500K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 50000h L80/B10 (Tq 25°C), 50000h L90/B50 (Tq 25°C) Nominal luminous flux: 13342lm Luminaire luminous efficiency: 150lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 89W Energy efficiency class/light source: C Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 25°C) Ambient temperatur: ta -20°C to 25°C Special properties: Ready for IoT UGR lat./long.: max. 25.1 / 25.1 Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGVCDA EP /1500 LED 13000 865 DALI2 vw RAL 9016 Article number: 19565006940 Product deep link: https://www.regiolux.de/en/article/19565006940 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	6500 K
Nominal lamp power	89.1 W	CRI	80
Total flux	13342 lm	LOR	100%
Luminous efficacy	150 lm/W	Total power	89.1 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 89.1 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White