


Product data sheet

LIGHTPOD V2 4300 30° E 04 940 - L
19.9904.0006.04
LUXIONA



Indoor luminaire. Assembly: mounted on a three-phase track. The body material is aluminum. Colour - RAL 9005 (black). Luminaire dimensions: Ø90 x 160 mm. Diffuser: PMMA lens. Beam angle: (C0-C180) / (C90-C270) - 31,6° / 31,8°. Light source type: LED. Colour of the light 4000 K. SDCM=6. CRI>90. Lifetime of LED sources: 60000 h L80/B10. Luminaire luminous flux: 4384,8 lm. Power of luminaire: 34,1 W. Luminaire's light efficiency: 128,6 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 28 (B10), 49 (B16), 29 (C10), 47 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: II. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	34.1 W	LOR	83%
Lamp flux	4385 lm	Total flux	3660 lm
Luminous efficacy	129 lm/W	Total power	34.1 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.30 in
Diameter: 3.54 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 34.1 W
Appliance Class: II

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F