


Product data sheet

SLOIN T SL LED5200-840 L3048 PC
42183675
ZUMTOBEL



LED light line with DALI-controllable LED converter, with cover to 50m from one piece; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 4960 lm, Luminaire efficacy: 105 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Luminaire of aluminium, white powder coated. Luminaire with completely uniform appearance due to polycarbonate cover. Luminaire consists of housing and continuous optic of polycarbonate. For installing in module ceilings with 12 mm edges and for installing in plasterboard ceilings. Armstrong® TECH ZONE compatible with ceiling types with width 100 mm. Includes gear tray, wiring, and end-cap set. Luminaire wired with halogen-free leads and covers are due to norm classified as TP(a). Degree of protection: IP40 below (IP20 above). Dimensions: 3048 x 100 x 134 mm weight: 9.3 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	47.2 W	CRI	80
Total flux	4960 lm	LOR	100%
Luminous efficacy	105 lm/W	Total power	47.2 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 120.00 in
Width: 3.94 in
Height: 5.28 in
Weight: 9.3 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 47.2 W
Voltage: 220-240 V AC
Controller: DALI
Appliance Class: I

Protection

IP: 20
IK: 07
Designation labels: CE, ENEC