


Product data sheet

SPIKE GRAPHITE W/ OUTLET 840LM 2700K RA>80 TRAILING EDGE DIMMING
7021986239317
SG ARMATUREN



Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct Light technic LED 10W 2700K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP44 IK08 Materials and finish Housing: Aluminium Colour: Graphite Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 10 W | LOR | 100% |
| Lamp flux | 840 lm | Total flux | 840 lm |
| Luminous efficacy | 84 lm/W | Total power | 10 W |
| CCT | 2700 K | | |
| CRI | 80 | | |

Mounting mode

Wall mounted

Shape and measurements

Length: 6.53 in

Width: 6.01 in

Height: 6.69 in

Adjustability

Fixed

Electric

System power: 10 W

Appliance Class: I

Protection

IP: 44

IK: 08