

# Product data sheet


DEFINE LED WALL MOUNT LUMINAIRE  
S122RDIW-S485D970U930-4F0-1E-UDD-F  
COOPER LIGHTING



IP  
47

Wall Mount Slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K & 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx and Stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 45.2 W   | CRI         | 90     |
| Total flux         | 4542 lm  | LOR         | 100%   |
| Luminous efficacy  | 100 lm/W | ULOR        | 69%    |
|                    |          | Total power | 45.2 W |

## Mounting mode

Wall mounted

## Shape and measurements

Length: 48.00 in

Width: 2.00 in

Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 45.2 W

## Protection

IP: 47