Product data sheet


DOWNLIGHTS - COMFORT EVO 4000K
ACOM1/1 + ACOM/TR/B/1 (13W 4000K)
ANSELL LIGHTING



IP 44

ACOM1/1 + ACOM/TR/B/1 Comfort Evo • Economic high performance CCT selectable IP44 downlight suitable for commercial and healthcare applications • Intelligent and eco-friendly 3 part design allows end user the choice of either black or white reflector and trim accessories to add to the downlight (ACOM*/1), offering great customisation and product upgradability • Deep cut-off angle for glare control and comfort • CCT selectable between 3000K and 4000K and power selectable; offering a choice of 2 outputs, in one luminaire • Downlight design allows installation into existing hole cut-outs of 210mm • Anti-Ligature kit available for installation in secure environments such as healthcare and educational facilities • Polycarbonate housing with unique thermal management for durability and optimum lifespan • Dimmable and Emergency options, standard and Self-Test Emergency available using the Hawk Kit Emergency Pack • LED lifespan L80 60,000 hours • Suitable for internal use only • 5 Year Product Warranty • IP44

Light output 1



1 x LED

Nominal lamp power	13.31 W	LOR	100%
Lamp flux	1519 lm	Total flux	1519 lm
Luminous efficacy	114 lm/W	Total power	13.31 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.20 in
Diameter: 9.06 in

Adjustability

Fixed

Design

Designer: Dominic Harkness

Electric

System power: 13.31 W

Protection

IP: 44