



Product data sheet

X-LINE LED COMPACT 2600 MICRO-PRM E 34 840 / L-1132MM
19.4189.2121.34
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings using accessories. The body material is aluminum. Colour - RAL 9016 (white). Luminaire dimensions: 1132 x 63 x 74 mm. Weight 2,13 kg. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA). The efficiency of the optical system is 75,32%. Beam angle: (C0-C180) / (C90-C270) - 82,8° / 97,2°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 90000 h L80/B10. Luminaire luminous flux: 2303 lm. Power of luminaire: 16,4 W. Luminaire's light efficiency: 140,4 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 22 (B10), 34 (B16), 33 (C10), 54 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP44. Impact resistant: IK04. Protection against electric shock: I.

Light output 1



1 x LED			
Nominal lamp power	16.4 W	LOR	83%
Lamp flux	3058 lm	Total flux	2552 lm
Luminous efficacy	186 lm/W	Total power	16.4 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.57 in
Width: 2.48 in
Height: 2.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 16.4 W
Appliance Class: I

Protection

IP: 44
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F