


# Product data sheet

TKGC L35 30° LE3  
TANEK CORNICE GLASS EMERGENCY  
DEXTRA




Tanek Glass Cornice - 1500mm, IP65, IK10 Cornice mounted luminaire, constructed from robust 1.2mm CR4 steel, toughened glass diffuser, weather resistant and salt spray tested, tamper resistant diffuser fixings, two 20mm side cable entries. Options: LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode\* RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode\* \*Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off. WH - White Finish BL - Black Finish C83 - CRI 80, 3000K

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20.3 W	CRI	80
Total flux	2491 lm	LOR	100%
Luminous efficacy	123 lm/W	ULOR	4%
		Total power	20.3 W

## Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	367 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	4%
		Total power	3 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 23.62 in

Width: 7.87 in

Height: 4.72 in

## Electric

System power: 23.3 W

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

## Adjustability

Fixed

## Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

## Protection

IP: 65

IK: 10

Resistant to impact of balls

Designation labels: CE