

Product data sheet

TOLDBOD 155 WALL 40W E14


5743145502

LOUIS POULSEN



Tolddod 155 Wall Design : Louis Poulsen Lighting A/S Concept : The light is directed 100% downwards, and the shade has a matt white painted inside which emits a soft, diffused, comfortable light. The fixture fulfils full cut-off criteria. Finish : Aluminium coloured with textured surface or black with textured surface, powder coated. Material : Fixture head: Chilled casting aluminium. Shield: Laser cut acrylic satine. Wall box: Die cast aluminium. Arm: Chilled casting aluminium. Mounting : Terminal block: 1x3x2.5mm². Cable entries: 2x bottom + 3x rear entries for Ø 10-14.5mm cable. Looping: Approved, max. 3x1,5mm². Class : Ingress protection IP44. Electric shock protection I w. ground. Weight : Max. 1.5kg.

Light output 1



1 x General service incandescent lamp

Nominal lamp power	40 W	LOR	69%
Lamp flux	400 lm	Total flux	277 lm
Luminous efficacy	7 lm/W	Total power	40 W
CCT			
CRI			

Mounting mode

Wall mounted

Shape and measurements

Height: 6.10 in

Diameter: 6.22 in

Adjustability

Fixed

Electric

System power: 40 W

Appliance Class: I

Protection

IP: 44