


# Product data sheet

XENA 1 SIDE  
55-9945-34-CM  
LEDSC4



LedsC4 Xena 1 Side 55-9945-34-CMV4 Bollard for outdoor use. For grazing lighting. Includes 2 cable outlets to facilitate chain mounting. Structure material: Aluminium. Structure finish: Grey. Diffuser material: Polycarbonate. Diffuser finish: Matt. UV protection. Warranty: 5 Years. Product net weight (Kg): 0.73 Product width or diameter (mm): 204 Product height (mm): 48 Class 1. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: OSRAM. Maximum power of light source: 1.5W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG2. % de Flickering: <5%. Real flux (lm): 46. Real lm/W: 23. Voltage / frequency range: 100-240VAC, 50/60Hz. Voltage: 3. Equipment included: Yes. Total power: 2. Power factor: 0.40. Dimmable equipment included: ON-OFF.

## Light output 1



1 x LED			
Nominal lamp power	2 W	LOR	100%
Lamp flux	46 lm	ULOR	44%
Luminous efficacy	23 lm/W	Total flux	46 lm
CCT	4000 K	Total power	2 W
CRI	75		

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 5.59 in  
Width: 5.55 in  
Height: 1.57 in

## Adjustability

Fixed

## Electric

System power: 2 W  
Appliance Class: I

## Protection

IP: 66  
IK: 10