


Product data sheet

MOUNTING RAIL SPOTLIGHT MATRIX CRI > 90 26W 3000K ON/OFF SI
2000.8842 - MATRIX LED3100-930 40 SR TRAQ ONF
REGENT



Mounting rail spotlight Matrix for mounting directly onto the Traq Linear support profile, with LED, colour rendering index CRI > 90, system power: 26 W, luminous flux of luminaire 3100 lm, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, 1 integral control gear, ON/OFF, control gear box in die-cast aluminium, silver, reflector housing in die-cast aluminium, wide beam, (F), 40°, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0310), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class E Ø = 127 mm, L = 175 mm, B = 92 mm, A = 210 mm, pivotable 360°, swivelling 45°, length of module (TRAQ strip) 295 mm

Light output 1



1 x LED			
Nominal lamp power	26 W	LOR	100%
Lamp flux	3100 lm	Total flux	3110 lm
Luminous efficacy	119 lm/W	Total power	26 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 7.05 in

Width: 12.40 in

Height: 7.99 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Silver gray

Electric

System power: 26 W

Appliance Class: I

Protection

IP: 20