

Product data sheet


7.5W 3000K 60°
L05
MP LIGHTING



IP
66

Application Exterior/interior directional in-grade light for lighting walls, columns, architectural features or landscape features. Applicable for mounting into floors, walls, ceilings or other surfaces where a non-obtrusive luminaire is required. IP Rating 66 Mounting Comes with splice box, aluminum flange and level gauge. Can be buried in earth/gravel or cast into concrete/paving stone with or without mounting base. Electrical 1 Watt x 3 LED / 2.5Watt x 3 LED Powered by remote dimmable/non-dimmable driver(sold separately). *See website for recommended drivers *Remote emergency driver / inverter options available. Consult factory Power Consumption 3.0 Watt 7.5 Watt Light Output 3.0 Watt, 117~173lm 7.5 Watt, 189~275lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Solid anodized aluminum or stainless steel (316), suitable for walk-over and drive-over applications. RoHS compliant. Drive over 4400kg/9700lbs Weight 2.56lbs (1.16kg) (base extra)

Light output 1



1 x LED			
Nominal lamp power	7.5 W	LOR	55%
Lamp flux	189 lm	ULOR	55%
Luminous efficacy	14 lm/W	Total flux	104 lm
CCT	3000 K	Total power	7.5 W
CRI	80		

Mounting mode

Floor recessed

Electric

System power: 7.5 W

Shape and measurements

Length: 3.62 in
Width: 3.62 in
Height: 0.24 in

Protection

IP: 66

Adjustability

Fixed