


Product data sheet

EVELUX L 96/310/730 DALI NR
104592
TREVOS



light fitting resistant to dust, humidity and spraying water, suitable for roads, residential areas, parking areas and open spaces; light fitting suitable for lighting outdoor sports halls, certified for ball impact safety pursuant to DIN 18032-3; wide range of optional versions of the light fitting's optical system for diverse applications; digitally dimmable DALI driver (AC/DC); Body: aluminium alloy, black grey (RAL 7021); Diffuser: heat-strengthened safety glass; Connection: screw terminal block with disconnecter for conductors with maximum cross-section of 4 mm²; Power: 90,6 W; Luminaire flux: 13880 lm; Lifetime: L80/B20; 100000 hours; Impact strength: IK10; Ambient temperature: -40|45 °C; Weight: 10,1 kg;

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	90.6 W	CRI	80
Total flux	16140 lm	LOR	100%
Luminous efficacy	178 lm/W	ULOR	4%
		Total power	90.6 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 34.25 in

Width: 13.58 in

Height: 5.00 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: Anthracite / graphite

Designer: TREVOS

Electric

System power: 90.6 W

Ballast: ECG

Controller: DALI

Appliance Class: I

Protection

IP: 66

IK: 10

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -40...113°F