Product data sheet

LSRS8B/LSRSWM8B LED 8" SHALLOW ROUND CYLINDERS LSR8B50D010 EC8B509730 8LBS0LI

COOPER LIGHTING








Mounting: high bay/low bay ceiling, wall, stem or aircraft cable, Spun aluminum housing; Spun aluminum reflectors, 5 color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-6,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

Light output 1 (integrated)



| Lamp type | LED | CCT |
|--------------------|---------|-------------|
| Nominal lamp power | 53 W | CRI |
| Total flux | 4572 lm | LOR |
| Luminous efficacy | 86 lm/W | Total power |

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in Width: 3.94 in Height: 3.94 in

Adjustability

Fixed

Electric

System power: 53 W

Protection

IP: 47

3000 K 100 100% 53 W