



# Product data sheet

FLEX STRIP HD RGB 5M  
L6507  
PROLED (MBN GMBH)




The PROLED FLEX STRIPS are perfect for indirect lightning, as custom made versions for fair or shop applications as well as for all kinds of illumination. Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS offer a wide spectrum of application possibilities. - 3 colours in one LED, therefore 100% smooth colour mixing. - High flexibility - adaptable to round shapes. - Also available in 20m reels. Please pay attention to the maximum length (5m) per power input. - Installation with 3M adhesive tape on the strip's backside (self adhesive). - dimmable, autom. colour change, controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies/controller

## Light output 1 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	5 W	CRI	-50
Total flux	100 lm	LOR	100%
Luminous efficacy	20 lm/W	Total power	5 W

## Light output 2 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	4.8 W	CRI	-18
Total flux	400 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	4.8 W

Light output 3 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	4.8 W	CRI	-29
Total flux	160 lm	LOR	100%
Luminous efficacy	33 lm/W	Total power	4.8 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.37 in

Width: 0.39 in

Height: 0.12 in

Adjustability

Fixed

Electric

System power: 14.6 W

Controller: Dimmable 1..10V, DMX, DALI

Appliance Class: III

Protection

IP: 20

Other operating numbers

Ambient temperature range: 14...113°F