Product data sheet


163 LED EMERGENCY LIGHT FITTING
163 15L60G2/3 865 MA (16307 0007)
SCHUCH



IP 65 IK 06


LED emergency light fitting, 42 W, 5970 lm, 142 lm/W, Self-contained battery, Self test, Emergency operating time 3 h, 830 lm, Class I, IP65, symmetrical wide beam, 6500 K, CRI≥ 80, Ta 0 °C/+30 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PMMA satined, Closure Plastic, Housing Glass fibre reinforced polyester, Colour grey. LED damp-proof emergency light fitting with self-contained battery and automatic monitoring according to EN62034. Glass fibre reinforced polyester housing, diffuser, foamed gasket and clips, incl. two safety clips. Powder-coated reflector with ECG, highly efficient Zhaga LED modules and LED covers (protection against contact). NiCd battery with electronic charger, short circuit protection, reverse battery protection and deep discharge protection. Automatic monitoring with optical indication of the test results. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1572,00 mm, Width/Diameter 116,00 mm, Height 88,00 mm, Net weight 3,50 kg.

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	42 W	CRI	80
Total flux	5970 lm	LOR	100%
Luminous efficacy	142 lm/W	ULOR	7%
		Total power	42 W

Light output 2 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	42 W	CRI	80
Total flux	5970 lm	LOR	100%
Luminous efficacy	142 lm/W	ULOR	7%
		Total power	42 W

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 61.89 in
Width: 4.57 in
Height: 3.46 in

Electric

System power: 84 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 65

IK: 06

Designation labels: CE