


Product data sheet

BASIC SUPERFLAT SEMI RECESSED - L7
BL70SE-840H-D500
LIGHTNET



Semi Recessed LED luminaire for ceilings with cut-out openings. Direct only light distribution. Surrounding mounting frame with only 18mm visible overall height. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. Recessed luminaire incl. mounting brackets. On request: Integration of emergency lighting components, sensor technology.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	82
Total flux	4030 lm	LOR	100%
Luminous efficacy	144 lm/W	Total power	28 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 19.69 in

Diameter: 19.69 in

Adjustability

Fixed

Electric

System power: 28 W

Protection