Product data sheet

ODESSA 19 FLOODLIGHTS,PROJECTORS AND COLUMN
OD-21041-VW-8030
LIGMAN



IP 66 IK 08

- Lamp COB - CCT / CRI 3000K CRI80, 4000K CRI80 - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry, through wiring upon request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear - Maximum wind load resistance is 140 km/h

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	70 W	CRI	80
Total flux	7518 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	100%
		Total power	70 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	70 W	CRI	80
Total flux	7518 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	100%
		Total power	70 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	70 W	CRI	80
Total flux	7518 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	100%
		Total power	70 W

Mounting mode

Pole integrated

Shape and measurements

Height: 39.37 in
Diameter: 7.48 in
Weight: 6 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 210 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C