

Product data sheet

SIDELITE SQUARE
311635.004
RZB




IP
40

IK
03

Series: Sidelite Type of Protection: IP 40 Protection Class: I Voltage: 100 - 240 V / 50 - 60 Hz Fitting sheet steel powder-coated, frame aluminium anodised, diffuser plastic, opal. Steel cable suspension infinitely adjustable to 3000mm, with conical canopies. Converter integrated. Sideways light input with LED, lamps (LED) included in delivery. Available Colours: anodised aluminium Type of Installation: Pendant Dimensions: L 1198, B 298, H 46 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 4300lm System power: 48W Beam Angle: 111° Inrush current: 25,9A Unified Glare Ratio: 21,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	48 W	CRI	80
Total flux	4300 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	48 W

Mounting mode

Pendant

Electric

System power: 48 W

Shape and measurements

Length: 11.73 in
Width: 47.17 in
Height: 0.79 in

Protection

IP: 40
IK: 03

Adjustability

Fixed