Product data sheet


INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I0-7M631-04L07-6507540 OLYMP 2.0 GL 75 W 75W 4000K 60°
VARTON



IP 65 IK 08

Medium-power Industrial luminaire with wide range of wattage and optics. Housing: heatsink made of extruded aluminum, assembly and mounting elements made of steel. Secondary optics - PMMA/PC. Tempered glass. Installation: Surface-mounted using an adjustable bracket. Angle of rotation: 0° to 180°, step of 7,5°. The luminaire has a wire for connecting to the mains. Wire length 0.3 meters. Application: Outdoor areas. Industrial facilities. Warehouses and fire hazardous zones classified as P-IIa according to Electrical Installations Regulations. Input voltage (AC, 50Hz): 100...305 AC frequency: 50 Input voltage (DC): 130...300 Flicker: 5 Power factor: 0,95 Climatic modification and category of placement: УХЛ2 Protection class: I Ingress protection (IP): IP65 Impact resistance: IK08 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/olymp-gl-2-0/olymp-gl-2-0-75-vt/svetodiodnyy-svetilnik-varton-promyshlennyy-olymp-gl-2-0-75-vt-4000-k-ip65-60-gradusov-rasseivatel-z/

Light output 1



1 x LED

Nominal lamp power	75 W	LOR	100%
Lamp flux	11250 lm	Total flux	11251 lm
Luminous efficacy	150 lm/W	Total power	75 W
CCT	4000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 21.06 in
Width: 3.46 in
Height: 6.69 in

Adjustability

Fixed

Electric

System power: 75 W

Protection

IP: 65
IK: 08