
Product data sheet


DEECOS P MINI
911519.004.1.76_982648.002
RZB



IP 20 IK 06

Series: DEECOS P mini Cylindrical pendant luminaire. Housing made of die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel, with magnetic attachment. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. Transparent pendant cable 5 m, can be shortened, with integrated steel cable. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Suitable for accessory Deecos P Tube cylinder extensions 0.5 m, 0.75 m or 1 m. Colour: silver Diameter: 87 mm Height: 195 mm Suspension length: 5000 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 90 System power: 20 W Rated luminous flux: 2600 lm Beam angle Down: 67° Luminous efficiency: 130 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	1380 lm	LOR	67%
Luminous efficacy	69 lm/W	ULOR	14%
		Total power	20 W

Mounting mode

Pendant

Shape and measurements

Height: 7.68 in
Diameter: 3.43 in

Adjustability

Fixed

Electric

System power: 20 W

Protection

IP: 20
IK: 06