
Product data sheet

VISION SUSPENDED - G2
VG2AEE-840M-L2055-Y
LIGHTNET



LED pendant luminaire. Direct-indirect or direct-only light distribution. Light channel made of aluminium profile with 130mm width. Precise length production according to specifications possible. Surface natural anodised or white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen and satin louver for office purposes. Opal diffuser made of acrylic glass for general lighting. Wallwasher for homogeneous vertical illuminance. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable Y-cord suspension with transparent power supply cable. On request: Integration of emergency lighting components.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	75 W	CRI	82
Total flux	6580 lm	LOR	100%
Luminous efficacy	88 lm/W	Total power	75 W

Mounting mode

Pendant

Shape and measurements

Length: 80.91 in
Width: 5.12 in
Height: 2.17 in

Adjustability

Height adjustable

Electric

System power: 75 W

Protection