

# Product data sheet


URBINO LED 36W 4400LM 5700K IP66 O6L - FOR PEDESTRIAN CROSSINGS, LEFT SIDE TRAFFIC GRAY II  
130222.5L142.091

LUG



Professional streetlight luminaire for LED light sources. High efficacy to 156 lm/W Mounting: on pillar  $\varnothing 60/48\text{mm}$ , on pillar  $\varnothing 76\text{mm}$  - modification .829, on outriggers  $\varnothing 60/48\text{mm}$ , on outriggers  $\varnothing 76\text{mm}$  - modification .829. Body: high pressure die-cast aluminum. Lateral Surface Wind Exposed: 0.039 m<sup>2</sup>. Power supply efficiency >95% Power: 220-240V 50/60Hz. Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, twilight sensor, knife switch, 10kV surge protection, NTC. Additional information: Tilt adjustment: -15° to +15° (every 5°). Additional equipment: additional anti-corrosive protection (index extension: .985), access to the driver chamber without the use of tools (index extension: .825), luminaire with holder for mounting on a  $\varnothing 76\text{mm}$  pillar (index extension: .829). Other remarks: the pole and boom are not part of the luminaire. Warranty: 5 years. Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenades, cycle paths. Type of optics: O6L - for pedestrian crossings, left side traffic

## Light output 1 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	36 W	CRI	70
Total flux	4400 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	36 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 21.65 in

Width: 9.84 in

Height: 3.94 in

## Adjustability

Tiltable

## Design

Color of housing: Silver gray

## Electric

System power: 36 W

Appliance Class: II

## Protection

IP: 66

IK: 09