

Product data sheet

6001/542-9510-15-131

220903


STAHL



IP
66


Light Fitting for Fluorescent Lamps EXLUX 6001 2x36W Explosion protection: Gas: Ex d e IIC T4 Gb or Ex db eb IIC T4 Dust: Ex tb IIIC T80 °C Db or Ex tb IIIC T80 °C Certificates Gas: PTB 13 ATEX 2004 Dust: PTB 13 ATEX 2004 Rated voltage: AC: 220 (- 10%) ... 240 (+ 10%) V, 50 / 60 Hz, DC: 198 ... 254 V/ 1-lamp: 176 ... 264 V Ambient temperature: -30 ... +50 °C Material: Enclosure: glass fibre reinforced polyester resin Cover: Polycarbonate Troughwiring: 5 conductors

Light output 1



2 x Fluorescent lamp tubular T5

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 36 W | Socket | G13 |
| Lamp flux | 3350 lm | LOR | 100% |
| Luminous efficacy | 93 lm/W | Total flux | 6700 lm |
| CCT | 3000 K | Total power | 72 W |
| CRI | 85 | | |



2 x Fluorescent lamp tubular T5

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 36 W | Socket | G13 |
| Lamp flux | 3350 lm | LOR | 100% |
| Luminous efficacy | 93 lm/W | Total flux | 6700 lm |
| CCT | 4000 K | Total power | 72 W |
| CRI | 85 | | |

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 51.50 in

Width: 7.23 in

Height: 5.04 in

Adjustability

Fixed

Electric

System power: 72 W

Protection

IP: 66