
# Product data sheet


QUADRO OFFICESPECIAL SUSPENSION DI/ID SILVER VDT 3
T65H33X-9006C2940H3D
PLANLICHT



IP 20


LED HO 4000K 93W 8109lm DALI CRI90 https://katalog.planlicht.com/en-gb/fam-quadro/

## Light output 1 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 23.25 W | CRI | 90 |
| Total flux | 2027 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | ULOR | 34% |
| | | Total power | 23.25 W |

## Light output 2 (integrated)




| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 23.25 W | CRI | 90 |
| Total flux | 2027 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | ULOR | 34% |
| | | Total power | 23.25 W |

## Light output 3 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 23.25 W | CRI | 90 |
| Total flux | 2027 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | ULOR | 34% |
| | | Total power | 23.25 W |

## Light output 4 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 23.25 W | CRI | 90 |
| Total flux | 2027 lm | LOR | 100% |
| Luminous efficacy | 87 lm/W | ULOR | 34% |
| | | Total power | 23.25 W |

### Mounting mode

Pendant

### Shape and measurements

Length: 1.97 in
Width: 132.48 in
Height: 2.60 in

### Adjustability

Fixed

### Electric

System power: 93 W

### Protection

IP: 20