


Product data sheet

STORMBELL 80 SUT 1500 WW MFL BK/WH+ ACC. BELL STORMBELL 80 Ø86X50 WH
ST18STLOMF930NBW+S8BE86W
LAMP



Downlight to suspend on TRACK 220V rail model STORMBELL 80 SUT 1500 WW MFL BK/WH LAMP brand. Body made of injected aluminum with white/black/Materiality finish, and with black/opal polycarbonate ring, for decorative lighting effect and possibility of accessory color filter, depending on his model. COB LED 3000K color temperature and CRI90. Aluminium reflector MEDIUM FLOOD. Luminaire with ceiling rose and electronic equipment included. Insulation class I. LED life time: 50000 L90 B10. Compatible with 4 different models of hoods (accessories) that complete the luminaire. + Accessory for suspended luminaires modell ACC. BELL STORMBELL 80 Ø86x50 WH LAMP brand. Body made of aluminum with white/black/Materiality finish. + Accessory for suspended luminaires modell ACC. BELL STORMBELL 80 Ø86x50 WH LAMP brand. Body made of aluminum with white/black/Materiality finish.

Light output 1



1 x LED			
Nominal lamp power	14.7 W	LOR	100%
Lamp flux	1144 lm	Total flux	1141 lm
Luminous efficacy	78 lm/W	Total power	14.7 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Height: 5.31 in
Diameter: 3.39 in
Weight: 5.5 kg

Adjustability

Fixed

Electric

System power: 14.7 W
Appliance Class: I

Protection

IP: 20