

Product data sheet


泛光灯
PAK460101 PAK-L83-070A-AF-L
PAK



IP
65


专利圆弧型一体化设计，高压铸铝成型灯体，反射罩采用高纯阳极电镀铝，高强度钢化玻璃，安全活页装置，四角下压式锁扣设计，适配光源：70W/Rx7S非对称型 金卤/高压钠 IP等级：IP65 适用于建筑泛光照明、广告招牌照明、体育馆、货场、码头和庭院道路等照明。

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	5800 lm	LOR	71%
Luminous efficacy	46 lm/W	Total flux	4097 lm
CCT	2000 K	Total power	89 W
CRI	31		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	6500 lm	LOR	71%
Luminous efficacy	52 lm/W	Total flux	4592 lm
CCT	4000 K	Total power	89 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 7.28 in
Width: 12.63 in
Height: 3.89 in

Adjustability

Tiltable

Electric

System power: 89 W

Protection

IP: 65