# Product data sheet

BENTO AREA M
BENTO AREA-M-ASY13-24LED-4000K-4P6S-230 MA
RAGNI



IP 66

Made of aluminium and with symmetrical lines, Bento AREA is a functional floodlight with a minimalist design available in 3 sizes. Rectangular in shape, it has a compartment at the rear housing the control gear, which harmoniously joins the lighting section. It has a double compartmentalisation and is fully IP66. Fixed laterally with a lyre, it can be installed on crossbars and crowns as well as on the front. Bento AREA has 12 to 24 LEDs in the S version, 24 to 48 LEDs in the M version and 72 LEDs in the L version, with a colour temperature of 3000 K or 4000 K. It has optimised light distributions and is specially designed for sports lighting, car parks and tertiary areas. The Bento AREA luminaire incorporates the Zhaga standard in its design.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 33 W | LOR | 100% |
| Lamp flux | 5094 lm | Total flux | 5094 lm |
| Luminous efficacy | 154 lm/W | Total power | 33 W |
| CCT | 4000 K | | |
| CRI | 70 | | |

### Mounting mode

Pole top mounted, Pole integrated

### Shape and measurements

Length: 27.56 in
Width: 11.81 in
Height: 3.94 in

### Adjustability

Tiltable

### Electric

System power: 33 W

### Protection

IP: 66