Product data sheet

BASIC NEO WALL - A5
BA5OSE-830M-D200-WALL
LIGHTNET



LED surface-mounted luminaire for walls or ceilings. Direct only light distribution. Luminaire body made of aluminium profile with slender overall height of 38mm without additional spacers. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components, sensor technology, Casambi.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4 W	CRI	82
Total flux	309 lm	LOR	100%
Luminous efficacy	77 lm/W	Total power	4 W

Mounting mode

Wall mounted

Shape and measurements

Height: 7.87 in
Diameter: 7.87 in

Adjustability

Fixed

Electric

System power: 4 W

Protection