Product data sheet


703.24 DOWNLIGHT WIDE FLOOD 40º 3000K DALI BLANCO CUADRADO
70324330-483
SIMON LIGHTING



IP 20

703.24 Downlight Wide Flood 40º 3000K DALI Blanco Cuadrado Características técnicas: 0,2 kg CRI 80 IP 20 Certificaciones: 2006/95/CE - Directiva Baja Tensión. 2004/108/CE - Directiva CEM. UNE-EN 60598: 2005 Luminarias. UNE-EN 62031: 2009 Módulos LED para alumbrado general. Requisitos de seguridad. UNE-EN 61347-2-13: 2007 Dispositivos de control de lámpara. UNE-EN 55015:2007 Límites y métodos de medida de las características relativas a la perturbación radioeléctrica de los equipos de iluminación y similares. UNE-EN 61547 Equipos para alumbrado de uso general. Requisitos de inmunidad - CEM. UNE-EN 61000-3-2 Compatibilidad electromagnética (CEM). UNE-EN 61000-3-3 Compatibilidad electromagnética (CEM).

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	7.5 W	CRI	80
Total flux	650 lm	LOR	100%
Luminous efficacy	87 lm/W	Total power	7.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.23 in
Width: 3.23 in
Height: 2.52 in

Adjustability

Rotatable, Tiltable

Electric

System power: 7.5 W

Protection

IP: 20