


# Product data sheet

KATLA BL 1540MM PCO 1X46W 120° 6500LM  
5231015B  
PRACHT



Luminaire KATLA BL 1540mm PCO 1x46W 6500lm, class I, IP65, high-efficiency LEDs, wide beam, 4000K, RA > 80, Ta:-20°C/35°C, housing made of PC polycarbonate and cover made of PC-OPAL, EAN/GTIN:4018098391203. LED damp-proof surface-mounted luminaire, BEG-eligible, made of very narrow, translucent, opalized polycarbonate (IK08, impact-resistant) luminaire housing, with short, age-resistant silicone seals. Including 3x1.5mm<sup>2</sup> through-wiring ex works. Profile luminaire optimized for parking lots, basements and workshops. Extremely easy installation thanks to all-round renewed PRACHT SLIDER and variable fixing distances thanks to PRACHT CLAMP SYSTEM. Suitable for ceiling, horizontal wall, pendant and trunking mounting. Light colors, control, emergency lighting modules, REMADE and much more - We configure the PRO LINE according to your requirements

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	46 W	CRI	80
Total flux	6500 lm	LOR	100%
Luminous efficacy	141 lm/W	ULOR	3%
		Total power	46 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 60.63 in  
Width: 2.68 in  
Height: 2.80 in  
Weight: 1.2 kg

## Adjustability

Fixed

## Electric

System power: 46 W  
Appliance Class: I

## Protection

IP: 65  
IK: 08

## Other operating numbers

Ambient temperature range: -4...95°F