


Product data sheet

BOX DP D MO 3000K SENSOR BT
E7018308
CARDI



Box DP D sensor BT är en bra allmänljusarmatur i klassisk design med direkt ljusfördelning som fungerar bra i många olika miljöer. Armaturen har ett väl avbländat dubbelparaboliskt reflektorbländskydd som ger en mycket bra avbländning längs armaturen. Monteras dikt tak eller pendlas, pendelkit beställs separat. Stomme av lackerad stålplåt, dubbelparaboliskt bländskydd av aluminium och avskärmning av akryl. Två kabelinföringar Ø 19 mm i centrum på armaturens ovansida samt en Ø 19 mm kabelinföring i vardera ände, insticksplint i mitten av armaturen 5x2x2,5 mm². Pendelkit E79 183 86 beställs separat. Armaturen har en sensor EasyAir SNS210 MC från Philips med närvaro och dagsljuskontroll som driftsätts via en App. Box sensor BT kan grupperas eller användas individuellt beroende på var man vill använda armaturen. Länk till app: <https://apps.apple.com/us/app/philips-field-app-mc/id1484451186> alt. <https://play.google.com/store/apps/details?id=com.signify.masterconnect>

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	80
Total flux	5000 lm	LOR	100%
Luminous efficacy	119 lm/W	ULOR	7%
		Total power	42 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 48.23 in
Width: 5.91 in
Height: 2.76 in

Adjustability

Fixed

Electric

System power: 42 W
Appliance Class: I

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor

Protection

IP: 20