



Product data sheet

CIRCULAR DOWNWARD 2 RINGS (Ø900 Ø600)
CS4N-00V9AZRU05
LEDSC4




LedsC4 Circular Downward 2 Rings (ø900 ø600) CS4N-00V9AZRU05V1 Pendant for indoor use. For downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 9 Product width or diameter (mm): 900 Product height (mm): 6500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 72.5W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 4439. Real lm/W: 57. Voltage / frequency range: 100-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 77.5. Power factor: 0.90. Dimmable equipment included: 0-10V.

Light output 1



1 x LED			
Nominal lamp power	38.5 W	LOR	100%
Lamp flux	2133 lm	Total flux	2133 lm
Luminous efficacy	55 lm/W	Total power	38.5 W
CCT	2700 K		
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	52.5 W	LOR	100%
Lamp flux	2306 lm	Total flux	2305 lm
Luminous efficacy	44 lm/W	Total power	52.5 W
CCT	2700 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 1.77 in

Electric

System power: 91 W
Appliance Class: I

Protection

IP: 20

Adjustability

Fixed