



Product data sheet

X-LINE LED 1300 PLX E 24 830 LINE-S / L-562MM
19.4163.1111.24
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction or surface mounted on slings. The body material is aluminum. Colour - anodised aluminum. Dimensions: 562 x 63 x 74 mm. Weight 1,6 kg. Diffuser: PLX (PMMA opal). The efficiency of the optical system is 66,66%. Beam angle: (C0-C180) / (C90-C270) - 109° / 107,2°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 899 lm. Power of luminaire: 9 W. Luminaire's light efficiency: 99,9 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,9. Circuit load capacity: 23 (B10), 36 (B16), 35(C10), 60 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP44. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED			
Nominal lamp power	9 W	LOR	52%
Lamp flux	1349 lm	Total flux	707 lm
Luminous efficacy	150 lm/W	Total power	9 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.13 in

Width: 2.48 in

Height: 2.91 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 9 W

Appliance Class: I

Protection

IP: 44

IK: 04

Other operating numbers

Ambient temperature range: 41...86°F