# Product data sheet


PLRW L20 40 HF C84 SP*
PRO-LIGHT MINI - ROUND
DEXTRA



IP 20

Pro-Light MINI - PLRW L20 40 HF C84 SP*, 2000 lumen LED recessed luminaire, wall wash optic, square die cast aluminium body, white powder paint finish, extruded aluminium heat sink, high performance specular reflector aluminium faceted 40 degree beam reflector, retractive spring clips cater for ceiling thicknesses from 0.5mm to 30mm. *Also available in black (B) or silver/grey (G) finish instead of white (W). Dimming options: S Switch Dimming A Digital Addressable Lighting Interface (DALI) D Digital Dimming (DSI) Optional polo rings available upon request for retro-fit applications where existing ceiling cut outs need to be utilised. Due to constant changes in LEDs, Please check our website for current product specifications.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 15.1 W | LOR | 64% |
| Lamp flux | 2000 lm | Total flux | 1279 lm |
| Luminous efficacy | 132 lm/W | Total power | 15.1 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

### Mounting mode

Ceiling recessed

### Shape and measurements

Height: 6.73 in
Diameter: 5.39 in

### Adjustability

Fixed

### Electric

System power: 15.1 W

### Protection

IP: 20