

Product data sheet

MEGA TUBE
611873.0031.1
RZB




IP
65

IK
03

Series: Mega Tube Type of Protection: IP 65 Protection Class: I Voltage: 176 - 264 V / 0 Hz, 50 - 60 Hz Bollard tube Ø 115mm made of corrosion resistant Aluminium profile, powder coated. Recessed stainless steel fixing plate. Non-corrosive gear compartment made of mould-cast dual compound thermoplastic with integral TP gasket. Opal glass diffuser with silk-matte finish. Integral electronic gear. With membrane valve to minimize condensation. Connection box for max. 2 x 3 x 2,5mm² loop-in-and-out. Available Colours: anthracite metallic Type of Installation: ground installation Dimensions: D 115, H 1100 Lamp: LED Life time: 60000 h (L80B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 620lm System power: 10W Beam Angle: 180° Number of fittings B10A: 8 Number of fittings B16A: 13 Number of fittings C10A: 14 Number of fittings C16A: 22 Inrush current: 54A Unified Glare Ratio: 17,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	620 lm	LOR	100%
Luminous efficacy	62 lm/W	ULOR	55%
		Total power	10 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 23.62 in
Diameter: 4.53 in

Adjustability

Fixed

Electric

System power: 10 W

Protection

IP: 65
IK: 03