

# Product data sheet

VIVITA DECOR RING WITH SHADE HL 740 ASYM CLO ND2 CL1  
305051-463  
FAGERHULT



Installation Luminaire for assembly on a post, with post top Ø 60 mm. Connection Supplied with 5 m 3x1,5 mm<sup>2</sup> connection cable (H05RN-F). Design Body, heat sink and cover in cast aluminium. Diffuser of impact resistant UV-stabilised polycarbonate. Ballast integrated in the luminaire. Louvre Decor rings in acrylic (PMMA). Reflector Symmetrical reflector in acrylic (PMMA) or asymmetrical reflector in sheet metal. Light Distribution Symmetrical or asymmetrical. Dimming CLO (Constant Light Output) maintains the correct light from the luminaire for the duration of its service life. Night-time dimming 2, dims down for eight hours. Other options for light control available on request. Standard Colour Alu-grey (RAL 9006). LED-information Driver with integrated surge protection (DM: 6 kV. CM: 8 kV). Extra surge protection (DM and CM: 10 kV) available on request.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	30 W	CRI	70
Total flux	3129 lm	LOR	100%
Luminous efficacy	104 lm/W	ULOR	7%
		Total power	30 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 28.17 in  
Width: 28.35 in  
Height: 21.38 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 30 W

## Protection

IP: 66