

Product data sheet


KORA V (1-ARMED)
9.107.1132.05
LEIPZIGER LEUCHTEN



IP
55

One or double-bracket pole luminaire with intensive brightness (height 4.50 and 6.00 m) in order to illuminate streets and footpaths. - Attachment made of plexiglass XT, sandblasted on one side - Computer-optimized reflector systems for high-pressure lamps with clear glass tubular bulbs/DULUX lamps ensures excellent illumination - Special steel luminaire body and unit carrier, available painted in any RAL or DB colour without surcharge, or ground and passivated - Luminaire case fold out for lamp change - Adapter jack connection - Included pole door to take in a cable joint box - Scope of supply includes square pole, incl. special steel bracket and electrical supply element (intermediate unit, ignition unit, condenser) - Available for 3 fastening variants in the ground: flange sheet, flange sheet in order to pave over, or end piece, situated at the pole, to set in the ground Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	61%
Lamp flux	7200 lm	Total flux	4414 lm
Luminous efficacy	50 lm/W	Total power	88 W
CCT	3000 K		
CRI	90		

Mounting mode

Pole integrated

Electric

System power: 88 W

Shape and measurements

Length: 31.50 in

Width: 9.84 in

Height: 3.15 in

Protection

IP: 55