

Product data sheet

RONDOS MAXI
911637.002.2.76
RZB




IP
20

IK
06

Series: RONDOS maxi LED recessed projector in a modern design with no visible cooling ribs. Housing made of die-cast aluminium, powder-coated. Rotation range: 356°; swivel range: ± 35°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. Suitable for Recessed ceiling mounting. Installation without tools thanks to spring fastening system. Separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Through-wiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: traffic white, matt (RAL 9016) Diameter: 178 mm Height: 3 mm Cut-out diameter: 168 mm Recess height: 200 mm Luminaire: recess height: 140 mm Lamp: LED Socket: without socket Colour temperature: 2700K Colour rendering index (CRI): 92 System power: 25 W Rated luminous flux: 3150 lm Beam angle Down: 33° Luminous efficiency: 126 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	25 W	CRI	90
Total flux	3150 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	13%
		Total power	25 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.12 in
Diameter: 7.01 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: White

Electric

System power: 25 W

Protection

IP: 20
IK: 06