
Product data sheet


BRONCO WALL UP/DOWNLIGHT NARROW BEAM
5206-0-3-523-XX
UNILAMP



IP 65 IK 09

BRONCO is a vertical designed wall up and down light with high-power LED light source. It is protected from the ingress of dust and water and is used in both outdoor and indoor environments. Operating with high lumen output Led in 2700K, 3000K and 4000K 3 steps SDCM. BRONCO can illuminate many lighting tasks in modern architectural surrounds and can be widely used in illuminating columns and facades. The body components are made from extruded and LM6 die-cast aluminium which make it highly corrosion resistant to any extreme environment. BRONCO is designed and tested under ambient thermal condition Ta 40°C. Spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • Molded lens from renowned manufacturer. • Quick connector for easy installation. • Installation work has to be carried on according to the enclosed product manual.


Light output 1



1 x LED

Nominal lamp power	8.1 W	LOR	100%
Lamp flux	960 lm	ULOR	7%
Luminous efficacy	119 lm/W	Total flux	960 lm
CCT	2700 K	Total power	11 W
CRI	80		

Light output 2



1 x LED

Nominal lamp power	8.1 W	LOR	100%
Lamp flux	960 lm	ULOR	7%
Luminous efficacy	119 lm/W	Total flux	960 lm
CCT	2700 K	Total power	11 W
CRI	80		

Mounting mode

Wall mounted

Electric

System power: 22 W
Appliance Class: I

Shape and measurements

Length: 2.68 in

Width: 7.09 in

Height: 7.05 in

Adjustability

Fixed

Protection

IP: 65

IK: 09