


Product data sheet


DIFFUSER 17W 600MM 4000K CRI80
TLS-S40FD
COLORS



IP
20

1. Professional and diverse optical modules, including models with ultra-high light efficiency (130LM/W), UGR<19, and precise light control;
2. Modular design allows for flexible combination and assembly, providing a more convenient installation and maintenance experience;
3. Integrated wiring at the back, enabling single-end power supply for cascading up to 40 meters, eliminating the troubles of traditional wiring installations;
4. A high-quality, ultra-long flexible diffuser of 50 meters ensures uniform and flawless light distribution;
5. Dual-color temperature adjustable models, emergency lighting models, intelligent control systems, and microwave sensing modules, making lighting more intelligent and convenient;
6. Certified with CE/UKCA/RoHS/Reach, ensuring quality assurance;

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 3991 K |
| Nominal lamp power | 17 W | CRI | 81 |
| Total flux | 1870 lm | LOR | 100% |
| Luminous efficacy | 110 lm/W | Total power | 17 W |

Mounting mode

Pendant, Contact rail

Electric

System power: 17 W

Shape and measurements

Length: 23.62 in
Width: 1.57 in
Height: 1.38 in

Protection

IP: 20

Adjustability

Fixed