


Product data sheet

MIC 3 FLOODLIGHTS,PROJECTORS
MI-50384-M-40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour RGBW 30,40 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	9.2 W	CRI	80
Total flux	479 lm	LOR	100%
Luminous efficacy	52 lm/W	Total power	9.2 W

Light output 2 (integrated)




Lamp type	LED	CCT	0 K
Nominal lamp power	9.1 W	CRI	-50
Total flux	69 lm	LOR	100%
Luminous efficacy	8 lm/W	Total power	9.1 W

Light output 3 (integrated)



Lamp type	LED	CCT	7247 K
Nominal lamp power	9.4 W	CRI	-18
Total flux	466 lm	LOR	100%
Luminous efficacy	50 lm/W	Total power	9.4 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	6.9 W	CRI	-29
Total flux	252 lm	LOR	100%
Luminous efficacy	37 lm/W	Total power	6.9 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 12.87 in
Diameter: 7.76 in
Weight: 3.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 34.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C