



Product data sheet

FLUM060-S 228S-280I-135EE/840, S
228S-280I-135EE/840
HALLA




228S-280I-135EE/840, S Luminaire surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Rounded Size: 943 x 60 x 65 mm Type of installation: Surface, Suspended Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.34 W	CRI	80
Total flux	196 lm	LOR	100%
Luminous efficacy	84 lm/W	ULOR	2%
		Total power	2.34 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.34 W	CRI	80
Total flux	196 lm	LOR	100%
Luminous efficacy	84 lm/W	ULOR	2%
		Total power	2.34 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	2.34 W	CRI	80
Total flux	196 lm	LOR	100%
Luminous efficacy	84 lm/W	ULOR	2%
		Total power	2.34 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.34 W	CRI	80
Total flux	196 lm	LOR	100%
Luminous efficacy	84 lm/W	ULOR	2%
		Total power	2.34 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.34 W	CRI	80
Total flux	196 lm	LOR	100%
Luminous efficacy	84 lm/W	ULOR	2%
		Total power	2.34 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 7.09 in

Width: 2.36 in

Height: 2.56 in

Adjustability

Fixed

Electric

System power: 11.7 W

Appliance Class: I

Protection

IP: 20

IK: 01