Product data sheet


MARVIK 4 SURFACE FACADE LUMINAIRES
MV-30031-VW-VW-8040
LIGMAN



IP 65 IK 08


- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and frame - Pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear - Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible - MARVIK luminaires with uplight and colder than 3000K CCT do not meet the IDA certificationrequirements

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	1104 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	100%
		Total power	10 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	1104 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	100%
		Total power	10 W

Mounting mode

Wall mounted

Shape and measurements

Height: 7.87 in
Diameter: 4.13 in
Weight: 1.6 kg

Adjustability

Fixed

Electric

System power: 20 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C

Design

Color of housing: Black, White, Silver gray