Product data sheet


NEW TRIA® 68 DL, PHASE, AIRTIGHT
1007283+1007330
SLV



IP 20


The GU10 Connection Box is suitable for LED lights with a maximum of 10W and GU10 base. Easy installation thanks to quick installation box and strain relief.

Light output 1




1 x LED

Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	100%
Luminous efficacy	75 lm/W	Total flux	450 lm
CCT	2723 K	Total power	6 W
CRI	92		



1 x LED

Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	100%
Luminous efficacy	75 lm/W	Total flux	450 lm
CCT	3058 K	Total power	6 W
CRI	92		



1 x LED

Nominal lamp power	6 W	Socket	Gu10
Lamp flux	450 lm	LOR	100%
Luminous efficacy	75 lm/W	Total flux	450 lm
CCT	4033 K	Total power	6 W
CRI	93		

Mounting mode

Ceiling recessed

Electric

System power: 6 W
Controller: Dimmable 0..10V
Appliance Class: II

Shape and measurements

Length: 3.23 in

Width: 3.23 in

Height: 0.08 in

Weight: 0.2 kg

Adjustability

Rotatable, Tiltable

Protection

IP: 20